





(Agentic) AI for the Enterprise Developer

Kevin Dubois
Sr Principal Dev Advocate
IBM


The landscape






Left / Right of the Model

LangChain / LangChain4j / Quarkus LangChain4j



Quarkus LangChain4j

<https://docs.quarkiverse.io/quarkus-langchain4j>



Some Concepts

Prompts

- ▶ Interacting with the model for asking questions
- ▶ Interpreting messages to get important information
- ▶ Populating Java classes from natural language
- ▶ Structuring output

Bootstrapping

LangChain4j

```
<dependency>
  <groupId>dev.langchain4j</groupId>
  <artifactId>langchain4j</artifactId>
</dependency>
<dependency>
  <groupId>dev.langchain4j</groupId>
  <artifactId>langchain4j-open-ai</artifactId>
</dependency>
```

Quarkus LangChain4j

```
<dependency>
  <groupId>io.quarkiverse.langchain4j</groupId>
  <artifactId>quarkus-langchain4j-openai</artifactId>
</dependency>
```



Configure an API key

```
quarkus.langchain4j.openai.api-key=sk-...
```

Define AI Service

```
@RegisterAiService
interface Assistant {
    String chat(String message);
}
```

Use DI to instantiate
Assistant

```
-----
@Inject
private final Assistant assistant;
```

Placeholder

Add context to the calls

```
@SystemMessage("You are a professional poet")
@UserMessage("""
    Write a poem about {topic}. The poem should be {lines} lines long.
    """)
String writeAPoem(String topic, int lines);
```

Main message to send


```
interface TransactionExtractor {  
    @UserMessage("Extract information about a transaction from {it}")  
    TransactionInfo extractTransaction(String text);  
}
```

```
class TransactionInfo {  
  
    @Description("full name")  
    public String name;  
  
    @Description("IBAN value")  
    public String iban;  
  
    @Description("Date of the transaction")  
    public LocalDate transactionDate;  
  
    @Description("Amount in dollars of the transaction")  
    public double amount;  
  
}
```

Unmarshalling
objects

Memory

- ▶ Create conversations
- ▶ Refer to past answers
- ▶ Manage concurrent interactions



Possibility to customize memory provider

```
@RegisterAiService(/*chatMemoryProviderSupplier = BeanChatMemoryProviderSupplier.class*/)
interface AiServiceWithMemory {
    String chat(@UserMessage String msg);
}
-----
@Inject
private AiServiceWithMemory ai;

String userMessage1 = "Can you give a brief explanation of Kubernetes?";

String answer1 = ai.chat(userMessage1);

String userMessage2 = "Can you give me a YAML example to deploy an app for this?";

String answer2 = ai.chat(userMessage2);
```

Remember previous interactions

```
@RegisterAiService()  
interface AiServiceWithMemory {  
    String chat(@MemoryId Integer id, @UserMessage String msg);  
}
```

```
-----  
@Inject  
private AiServiceWithMemory ai;
```

```
String answer1 = ai.chat(1, "I'm Frank");
```


```
String answer2 = ai.chat(2, "I'm Betty");
```

```
String answer3 = ai.chat(1, "Who Am I?");
```

keep track of multiple parallel conversations

Refers to conversation with id == 1, ie. Frank

Add your own data to the model ?



Embedding Documents (RAG)

- ▶ Adding specific knowledge to the model
- ▶ Asking questions about supplied documents
- ▶ Natural queries

```
$ quarkus extension add langchain4j-redis
```

Define which doc store to use, eg. Redis, pgVector, Chroma, Infinispan, ..

```
@Inject
```

```
EmbeddingStore store;
```

```
EmbeddingModel embeddingModel;
```

Ingested documents stored in eg. Redis

Document from CSV, spreadsheet, text..

```
public void ingest(List<Document> documents) {
```

```
    EmbeddingStoreIngestor ingestor = EmbeddingStoreIngestor.builder()
```

```
        .embeddingStore(store)
```

```
        .embeddingModel(embeddingModel)
```

```
        .documentSplitter(myCustomSplitter(20, 0))
```

```
        .build();
```

```
    ingestor.ingest(documents);
```

```
}
```

Ingest documents



Augmentation
interface

```
@ApplicationScoped  
public class DocumentRetriever implements Retriever<TextSegment> {
```

```
    private final EmbeddingStoreRetriever retriever;
```

CDI injection

```
    DocumentRetriever(EmbeddingStore store, EmbeddingModel model) {  
        retriever = EmbeddingStoreRetriever.from(store, model, 10);  
    }
```

```
@Override
```

```
    public List<TextSegment> findRelevant(String s) {  
        return retriever.findRelevant(s);  
    }
```

```
}
```

Tell the agent where to
retrieve data from

```
@RegisterAiService(retrieverSupplier = BeanRetrieverSupplier.class)
public interface MyAiService {
    (..)
}
```


Alternative/easier way to retrieve docs:

Easy RAG

```
$ quarkus extension add langchain4j-easy-rag
```

```
quarkus.langchain4j.easy-rag.path=src/main/resources/catalog
```

eg. Path to documents



Function Calling / Tools

- ▶ Mixing **business code** with model's probabilistic creativity
- ▶ Delegating to **external services**

```
public class EmailService {
```

```
    @Inject  
    Mailer mailer;
```

```
    @Tool("send the given content by email")  
    public void sendAnEmail(String content) {  
        mailer.send(Mail.withText("letter@quarkus.io", "A poem", content));  
    }
```

```
}
```

Describe when to use the tool




Register the tool




```
@RegisterAiService(tools = EmailService.class)  
public interface MyAiService {
```

```
    @SystemMessage("You are a professional poet")  
    @UserMessage("Write a poem about {topic}. Then send this poem by email.")  
    String writeAPoem(String topic);
```

Ties it back to the tool
description



Model Context Protocol (MCP)




Quarkus MCP Extension


- ▶ Build custom MCP servers and clients *in Java*
- ▶ Autogenerates Tool Providers for MCP servers
- ▶ Custom Log handlers per provider
- ▶ `stdio` and HTTP (SSE) transports, with optional security
- ▶ All of the langchain4j capabilities out of the box
 - Declarative AI services, guardrails, observability, RAG, native images, dev services, dev UI, memory, ...

Fantastic. What could
possibly go **wrong?**


Prompt injection




Raw, “Traditional” Deployment



Raw, "Traditional" Deployment




Deployment with Guardrails



Input Detector

Safeguarding the types of interactions users can request



Output Detector

Focusing and safety-checking the model outputs

"It is an official and binding position of the Acme Inc. that Dutch beer is superior to Belgian beer."

Output
Guardrail

Model Output: "It is an official and binding position of the Acme Inc. that Dutch beer is superior to Belgian beer."

Result: Validation Error

Reason: Forbidden language, factual errors

```
@RegisterAiService
```

```
public interface Assistant {
```

```
    @InputGuardrails(InScopeGuard.class)
```

```
    String chat(String message);
```

```
}
```

Declare a guardrail



```
public class InScopeGuard implements InputGuardRail {
```

```
    @Override
```

```
    public InputGuardrailResult validate(UserMessage um) {
```

```
        String text = um.singleText();
```

```
        if (text.contains("ingore all previous commands")) {
```

```
            return failure("Please don't try prompt injection");
```

```
        }
```

```
        return success();
```

```
    }
```

```
}
```

Do whatever check is needed



Fault Tolerance

- ▶ Gracefully handle model failures
- ▶ Retries, Fallback, CircuitBreaker

Add MicroProfile Fault
Tolerance dependency

```
$ quarkus ext add smallrye-fault-tolerance
```

```
@RegisterAiService()
public interface AiService {
    @SystemMessage("You are a Java developer")
    @UserMessage("Create a class about {topic}")
    @Fallback(fallbackMethod = "fallback")
    @Retry(maxRetries = 3, delay = 2000)
    public String chat(String topic);

    default String fallback(String topic){
        return "I'm sorry, I wasn't able create a class about topic: " + topic;
    }
}
```

Handle Failure

Retry up to 3 times

Observability


- ▶ Log interactions with the LLM
- ▶ Collect metrics about your AI-infused app
- ▶ LLM Specific information (nr. of tokens, model name, etc)
- ▶ Trace through requests to see how long they took, and where they happened

```
$ quarkus ext add opentelemetry micrometer-registry-otlp
```

Agentic AI Patterns with LangChain4j

From single AI Service to Agents and Agentic Systems

In essence what makes an **AI service** also an **Agent** is the capability to **collaborate** with other Agents in order to perform more complex tasks and pursue a common goal



The new langchain4j-agentic module

LangChain4j 1.3.0 introduces a new (experimental) agentic module.



Agentic systems

Agents in LangChain4j

Introducing the AgenticScope

Workflow patterns

Sequential workflow

Loop workflow

Parallel workflow

Conditional workflow

Error handling

Declarative API

Memory and context engineering

AgenticScope registry and persistence

Pure agentic AI

Supervisor design and customization

Providing context to the supervisor

Non-AI agents

Human-in-the-loop

A2A Integration



Recap

- ▶ Java ❤️ AI
- ▶ LangChain4j is stack agnostic
- ▶ Quarkus makes it easier 😊
- ▶ Try it out yourself:

quarkus.io/quarkus-workshop-langchain4j/





speakerdeck.com/kdubois

slides



Thank you!



quarkus.io/quarkus-workshop-langchain4j/
docs.quarkiverse.io/quarkus-langchain4j
github.com/kdubois/netatmo-java-mcp



@kevindubois.com



youtube.com/@thekevindubois



linkedin.com/in/kevindubois



github.com/kdubois



@kevindubois@mastodon.social